



Features :

- 2:1 wide input range
- 1500VDC I/O isolation
- Built-in remote ON/OFF control
- · Built-in EMI filter
- · Protections: Short circuit / Overload
- · Cooling by free air convection
- · Five-sided shield metal case
- 100% full load burn-in test
- Low cost / High reliability
- 2 years warranty


SPECIFICATION

F© (E

ORDER NO.		DCW12A-05	DCW12B-05	DCW12C-05	DCW12A-12	DCW12B-12	DCW12C-12	DCW12A-15	DCW12B-15	DCW12C-15	
	DC VOLTAGE	±5V			±12V			±15V			
ОИТРИТ	CURRENT RANGE	±240 ~ ±1200mA			±100~ ±500mA			±80 ~ ±400mA			
	RATED POWER	12W									
	RIPPLE & NOISE (max.) Note.2	50mVp-p			60mVp-p			60mVp-p			
	LINE REGULATION Note.3	±0.5%									
	LOAD REGULATION Note.4	±0.5%									
	VOLTAGE ACCURACY	±2.0%									
	SWITCHING FREQUENCY	400KHz min.									
INPUT	VOLTAGE RANGE	A: 9 ~ 18VDC B: 18 ~ 36VDC C: 36 ~ 72VDC									
	EFFICIENCY (Typ.)	80%	80%	81%	84%	84%	84%	83%	84%	83%	
	DC CURRENT	Full load A: 1245mA B: 625mA C: 320mA									
	DO CONTREINT	No load A: 70mA B: 35mA C: 25mA									
	FILTER	Pi network									
	PROTECTION	Fuse recomm	Fuse recommended								
PROTECTION Note.5	OVERLOAD	110 ~ 180% rated output load									
		Protection type: Hiccup mode, recovers automatically after fault condition is removed									
	SHORT CIRCUIT	All output equipped with over current protection									
		Protection type: Hiccup mode, recovers automatically after fault condition is removed									
ENVIRONMENT	WORKING TEMP.	-40 ~ +71°C (refer to output load derating curve)									
	WORKING HUMIDITY	20% ~ 90% RH non-condensing									
	STORAGE TEMP., HUMIDITY	-40 ~ +105°C, 10 ~ 95% RH									
	TEMP. COEFFICIENT	±0.05% / °C (0 ~ 50°C)									
	VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes									
SAFETY & EMC	WITHSTAND VOLTAGE ISOLATION RESISTANCE	I/P-0/P:1.5KVDC									
	ISOLATION CAPACITANCE	I/P-O/P: 100M Ohms / 500VDC / 25°C/ 70% RH									
		2200pF max. Compliance to EN55022 Class A, FCC part 15 Class A									
	EMC EMISSION EMC IMMUNITY	Compliance to EN33022 Class A, PCC part 13 Class A Compliance to EN61000-4-2,3,4,5,6,8, light industry level, criteria A									
	REMOTE CONTROL		Power ON: R.C. ~ -Vin > 4VDC or open; Power OFF: R.C. ~ -Vin < 1VDC or short								
OTHERS	MTBF	600Khrs min. MIL-HDBK-217F (25°C)									
	DIMENSION	31.8*20.3*12.2mm (L*W*H) or 1.25"*0.80"*0.48" inch (L*W*H)									
	PACKING	18.5g									
PACKING		10.09									

■ Mechanical Specification


Unit:mm(inch)



■ Pin Configuration

Pin No.	Output					
1	R.C.					
2 & 3	-Vin					
9	COM					
11	-Vout					
14	+Vout					
16	COM					
22 & 23	+Vin					

■ Derating Curve



NOTE

- 1.All parameters are specified at normal input, rated load, 25℃ 70% RH ambient.
- 2. Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1 uf & 47 uf capacitor.
- 3.Line regulation is measured from low line to high line at rated load.
- 4.Load regulation is measured from 20% to 100% rated load.
- 5.Please prevent the converter from operating in overload or short circuit condition for more than 30 seconds.